

Survey of the Range Line through T. 46 N., bet. Rs. 59 and 60 E.

Chains 70.00	Leave bench, bears N. 20° E. and S. 20° W.; desc. 155 ft. on a NW. slope.																		
80.43	Intersect the S. bdy. of T. 47 N., R. 60 E. Set an iron post 3 ft. long, 3 ins. diam., 27 ins. in the ground, for the closing cor. of Tps. 46 N., Rs. 59 and 60 E., with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>TL47N</td><td></td></tr> <tr><td>R60E</td><td></td></tr> <tr><td>S31</td><td></td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>S1</td><td>S6</td></tr> <tr><td>C</td><td>C</td></tr> <tr><td>R59E</td><td>R60E</td></tr> <tr><td>TL46N</td><td></td></tr> <tr><td>1933</td><td></td></tr> </table> </div> <p>raise a mound of stone 2 ft. base, 1½ ft. high, S. of cor. From point of intersection the cor. of Tps. 47 N., Rs. 59 and 60 E., hereinbefore described, bears S. 89°08' W., 2.21 chs. dist. Land, rolling hills. Soil, shallow sandy loam surface, 3rd rate. Undergrowth, sagebrush, buckbrush, and grouse brush. Bunch grass. No timber. Grazing, fair.</p>	TL47N		R60E		S31		-----		S1	S6	C	C	R59E	R60E	TL46N		1933	
TL47N																			
R60E																			
S31																			

S1	S6																		
C	C																		
R59E	R60E																		
TL46N																			
1933																			

SUBDIVISION OF T. 46 N., R. 60 E.

	From the standard cor. of secs. 35 and 36, on the S. bdy. of Tp. 46 N., R. 60 E., which is an iron post 2 ins. diam., firmly set, mkd. and witnessed as described in book "A" this group. N. 0°13' E., on a governing section line which is parallel to the mean course of the E. bdy., bet. secs. 35 and 36. Over rolling benchland; asc. 25 ft. on a S. slope along the E. side of a shallow draw.						
2.80	Draw, course S. from N. 30° E.; asc. 160 ft. on a S. slope across the head of same draw.						
21.80	Spur, projects S. 20° E.; asc. 5 ft. on a SE. slope.						
32.30	Broad shallow draw, course S. 30° E. from NW.; asc. 90 ft. on a general S. slope.						
40.00	Set an iron post 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>¼</td><td></td></tr> <tr><td>S35</td><td>S36</td></tr> <tr><td>1933</td><td></td></tr> </table> </div>	¼		S35	S36	1933	
¼							
S35	S36						
1933							