


SUBDIVISION OF T. 46 N., R. 59 E.

642

Chains

- 21.40 Outcrop, bears NW. and SE.; asc. 170 ft. on a S. slope through scattered clumps of mahogany.
- 36.10 Road, bears N.20°W. and S.38½°E.; asc. 40 ft. on a S. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap mkd.



1933

from which

A balsam, 22 ins. diam., bears S.84¼°E., 148 lks. dist., mkd. ¼ S2 BT.


A mahogany, 14 ins. diam., bears S.24½°W., 541 lks. dist., mkd. ¼ S3 BT.

- 40.20 Small spur slopes S.70°W.; enter dense scrub aspen bearing E. and W.; continue along a W. slope through dense timber.
- 44.10 Slope changes to a SW. slope; asc. 50 ft.
- 46.80 Leave timber, bears SE. and W. about 1 ch., then S.; asc. 140 ft. on a SW. slope.
- 64.90 Top of slope, bears N.60°W. and SE.; asc. 10 ft. across a rolling top.
- 73.00 Top of broad spur, slopes NW.; across flat top.
- 76.20 Road, bears NW. and SE.; desc. 10 ft.
- 80.08 Intersect the S. bdy. of T. 47 N., R. 59 E.

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 2 and 3, with brass cap mkd.

T47N

S35



T46N R59E

1933

raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.

From this point the corner of secs. 34 and 35, T. 47 N., R. 59 E., which is an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears S.89°56'W., 5.26 chs. I alter the markings on this corner by adding S3 T46N R59E to the south half of brass cap.

Land, benchland cut by deep canyon. Soil, shallow sandy loam surface, 3rd rate. Timber, aspen, balsam and mahogany; undergrowth, sagebrush, buckbrush and yellow top, bunch grass. Grazing, fair.