

SUBDIVISION OF T. 45 N., R. 59 E.

Chains

from which,

A fir, 4 ins. diam., bears N. 58° E., 123 lks. dist.,
mkd. $\frac{1}{4}$ S 1 B T.

A pine, 3 ins. diam., bears N. 41° W., 177 lks. dist.,
mkd. $\frac{1}{4}$ S 2 B T.

Desc. 430 ft. over NE. slope.

41.80 Enter dense timber, bears SE. and NW.

57.38 Intersect 9th Stan. Par. N.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground,
for closing cor. of secs. 1 and 2, with brass cap mkd.

T46N R59E

S35

S 2	S 1
T45N	R59E

CC

1939

from which,

A fir, 8 ins. diam., bears S. 50° E., 42 lks. dist.,
mkd. T45N R59E S1 CC BT.

A pine, 4 ins. diam., bears S. 17½° W., 20 lks. dist.,
mkd. T45N R59E S2 CC BT.

From this point, the standard $\frac{1}{4}$ sec. cor. of sec. 35, bears West
14.10 chs. dist., a one inch iron post, mkd. and witnessed as des-
cribed in the official record.

Land, mountainous.
Soil, clay loam and rocky; 2nd and 3d rate.
Timber, fir, pine, mountain mahogany.
Undergrowth, sagebrush.
Grazing, good.

From the cor. of secs. 25, 26, 35 and 36.

West, on sectional correction line, bet. secs. 26 and 35. Desc.
950 ft. over broken W. slope.

35.00 Along S. slope at head of large draw, drains S.

39.94 Point for $\frac{1}{4}$ sec. cor. falls on steeply sloping surface rock, imprac-
ticable to establish a permanent monument. Asc. 370 ft. over E.
slope.

40.49 Set an iron post, 3 ft. long, 1 in. diam., over a cross cut in sur-
face rock in a mound of stone to top, for witness $\frac{1}{4}$ sec. cor., with
brass cap mkd.

S 26

$\frac{1}{4}$	WC
S 35	

1939

49.50 Rocky spur, projects S., desc. 540 ft. over W. slope.

65.20 Minor drain, course S. 30° W., asc. 250 ft. over SE. slope.