

SUBDIVISION OF T. 45 N., R. 59 E.

Chains

27.90

Head of Mary's River, 2 lks. wide, 1 in. deep, course S. 10° E., asc. 100 ft. over SE. slope.

32.00

Sidehill drain, course S. 50° E., asc. 350 ft. over E. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 30

S 31

1939

from which

A pine, 12 ins. diam., bears N. 10° E., 7 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.

A pine, 4 ins. diam., bears S. 87 $\frac{3}{4}$ ° W., 45 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.

Asc. 90 ft. over E. slope.

44.00

Spur, projects SE.; desc. 100 ft. over SW. slope.

55.30

Drain, course SE.; asc. 760 ft. over E. slope.

77.01

Target on Mary's River Peak at U. S. G. S. triangulation station, bears N. 3° 58' E., 16.60 chs. dist.

77.20

Spur, slopes S. 10° E., desc. 60 ft. over W. slope.

80.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for cor. of lots 1 and 2, sec. 31 and lots 7 and 8, sec. 30, with brass cap mkd.

S 30

7 8

2 1

S 31

1939

raise a mound

of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

Desc. 200 ft. over SW. slope changing to S. slope.

85.84

Intersect E. bdy. of T. 45 N., R. 58 E., at a point 10.62 chains South of the point for cor. of secs. 25 and 36.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 30 and 31, with brass cap mkd.

T45N T45N

R58E R59E

S36 S30

S31

1939

from which

A pine, 3 ins. diam., bears N. 76 $\frac{1}{2}$ ° E., 75 lks. dist., mkd. T 45 N R 59 E S 30 C C B T.

A pine, 3 ins. diam., bears S. 37° E., 51 lks. dist., mkd. T 45 N R 59 E S 31 C C B T.

The witness cor. of secs. 25 and 36, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record, bears North, 6.78 chs. dist. and the true point for corner North 10.62 chs.

Land, mountainous.