

Subdivision of T. 5 N., R. 65 E.

Chains.

sagebrush, scattering service-berry bushes, medium growth of cedar and pinon pine; desc.


14.30 Leave medium growth of timber, bears E. and W., and enter scattering.

14.83 Road bears N.60°E. to Pioche and S.60°W. to Hamilton, in head of hollow, draining S.60°W., 75 ft. below sec. cor.; asc. 15 ft.

32.40 Low spur, projects SW. about 15.00 chs. dist.; desc. 15 ft.

33.00 Draw, course SW.; asc. gradually 20 ft. to

40.00 On a S. slope, set an iron post, 3 ft. long, 1 in. dia., 22 ins. in the ground to solid rock and in a mound of stone for 1/4 sec. cor., with brass cap mkd:



from which,

A cedar, 8 ins. diam., bears S.50°45'E., 323 lks. dist., marked 1/4 S 2 B T. ✓

A cedar, 14 ins. diam., bears N.89°15'W., 122 lks. dist., marked 1/4 S 3 B T. ✓

Continue gradual ascent along E. side of draw, draining S.10°W.

66.48 Intersect the first St. Par. N., 5.51 chs. E. of the standard 1/4 cor. of sec. 34, hereinbefore described, and at the point of intersection, set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground for closing cor. of secs. 2 and 3, with brass cap mkd:



from which,

A cedar, 8 ins. diam., bears S.32°15'E., 150 lks. dist., marked C C T 5 N R 65 E S 2 B T, ✓

A cedar, 6 ins. diam., bears S.50°30'W., 164 lks. dist., marked C C T 5 N R 65 E S 3 B T. ✓