

Subdivisions of T. 18 N., R. 62 E.

Chains	
	From the cor. of secs. 1, 2, 35 and 36, on the north bdy. of the township, which is a limestone, 10x10x4 ins. in a mound of stone, marked and witnessed as described by the surveyor-general, S. 0° 01' E., bet. secs. 1 and 2. Desc. a very rough SW. slope over cliffs and crags, 675 ft. to,
20.50	Head of a deep gulch, course W., asc. NW. slope 30 ft. to,
20.75	Sharp spur, falls W., desc. SE. slope 35 ft. to,
24.00	Draw, course W., asc. NW. slope 100 ft. to,
31.90	Rocky, sharp spur, falls SW., desc. SW. slope 132 ft. to,
34.90	Head of draw, course W. along a very rough broken W. slope to,
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 24 ins. in a large mound of stone, on a solid ledge of rock, for $\frac{1}{4}$ sec. cor., with brass cap marked,
	$\frac{1}{4}$ S 2 S 1
	1918 ; raise a mound of stone,
	2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Desc. broken SW. slope 265 ft. to,
48.10	Head of a steep gulch, course SW., asc. NW. slope 30 ft. to,
50.60	Spur, falls SW., desc. SW. slope 250 ft. to,
56.40	Head of a large gulch, course W., asc. NW. slope 70 ft. to,
64.60	Rocky spur, falls W., desc. SW. slope 136 ft. to,
73.50	Rocky spur, falls SW., desc. a rough SW. slope 20 ft. to,
80.00	Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in a mound of stone, 5 ft. base, on a solid ledge, for cor. of secs. 1, 2, 11 and 12, with brass cap marked,
	T 18 N R 62 E S 2 S 1 S 11 S 12
	1918 ; from which,
	A pine, 6 ins. in dia., bears N. 74 $\frac{3}{4}$ ° E., 26 lks. dist., marked, T 18 N R 62 E S 1 BT
	A pine, 6 ins. in dia., bears S. 28 $\frac{1}{4}$ ° E., 36 lks. dist.,