

## Retracement of the East Bdy. of T. 15 N., R. 67 E.

Chains	
160.00	No trace of the original corner of secs. 25, 30, 31 and 36.
200.00	No trace of the original $\frac{1}{4}$ sec. cor., bet. secs. 25 and 30.
240.00	No trace of the original cor. of secs. 19, 24, 25 and 30.
280.00	No trace of the original $\frac{1}{4}$ sec. cor., bet. secs. 19 and 24.
320.00	No trace of the original cor. of secs. 13, 18, 19 and 24.
360.00	No trace of the original $\frac{1}{4}$ sec. cor., bet. secs. 13 and 18.
403.45	Fall 12 lks. W. of the original cor. of secs. 7, 12, 13 and 18, which is a cedar post, marked and witnessed as described by the surveyor-general. The bearing of the true line bet. the original cor. of secs. 1, 6, 7 and 12, of T. 14 N., Rs. 67 and 68 E., and this corner is N. $9^{\circ}$ 01' E., and the distance is 403.45 chs. Continue North, on same line,
481.59	Fall 92 lks. W. of the original corner of secs. 1, 6, 7 and 12, which is a cedar post, marked and witnessed as described by the surveyor-general.
550.07	Fall 365 lks. W. of the original closing cor. of Ts. 15 N., Rs. 67 and 68 E., which is a granite stone, 8x8x8 ins. above ground, marked and witnessed as described by the surveyor-general. This corner was re-established by Surveyor Pray, in 1909.

Dependent Resurvey of the East boundary of T. 15 N., R. 67 E., and Independent Resurvey of the West bdy. of T. 15 N., R. 68 E.

From the original corner of secs. 1, 6, 7 and 12, on the Range line bet. Ts. 14 N., Rs. 67 and 68 E., previously described,  
N  $0^{\circ}$  01' E. on a blank line for distance only,  
80.69 At the proportionate position for the original corner of Ts. 14 and 15 N., Rs. 67 and 68 E.,  
Set an iron post, 3 ft. long, 3 ins. in dia., 14 ins. in ground, to bed rock, in a mound of stone, with 5 ft. base, for cor. of Ts. 14 and 15 N., Rs. 67 and 68 E., with