


Dependent Resurvey of the Range line bet. Ts. 15 N.,
R.s. 67 and 68 E.


Chains

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
ground, for $\frac{1}{4}$ sec. cor., with brass cap marked,



1918 raise a mound of
stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

41.83 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
ground, for $\frac{1}{4}$ sec. cor., with brass cap marked,




1918; raise a mound of
stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

45.60 Drain, course W. over rolling W. slope

75.40 Drain, course W.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in
ground, for cor. of secs. 6 and 7, with brass cap
marked,



1918; raise a mound of
stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

Land, rolling flat.

Soil, 2nd and 3rd rate, washed gravel and sand.

Timber, none.

Undergrowth, low sage brush and greasewood.

N. $0^{\circ}35'$ E., on true line on the West bdy. of sec. 6.

Over level land.

.90 The original corner of secs. 1, 6, 7 and 12, which is a
cedar post, witnessed as described by the surveyor
general. This corner will now refer to T. 15 N., R. 67 E.,
only. I perpetuate it as follows;