

Survey of the Third Standard Parallel North
thru Range 68 East.

C hains

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 18 ins. in ground, in a mound of stone, with 5 ft. base, (for standard cor. of secs. 35 and 36, with brass cap marked,

T 16 N R 68 E
S C
S 35 | S 36

1918 ; from which,

A pine, 16 ins. in dia., bears N.25°E., 93 lks. dist., marked, T 16 N R 68 E S 36 BT SC

A pine, 16 ins. in dia., bears N.57°W., 40 lks. dist., marked, T 16 N R 68 E S 35 BT SC

Land, mountainous.

Soil, 4th rate, very rocky cliffs and ledges.

Timber, pine and juniper.

Undergrowth, mountain mahogany, service berry bushes.

East, on the south boundary of sec. 36.

Asc. NW. slope 60 ft. to,

3.50 Spur, falls S., desc. SE. slope 145 ft. to,

11.60 Large draw, course S.10°W., asc. NW. slope 250 ft. to,

20.50 Spur, falls S., desc. SE. slope 137 ft. to,

34.27 Draw, course SW., asc. SW. slope 120 ft. to,

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in ground, (for standard $\frac{1}{4}$ sec. cor.) with brass cap marked,

S C

$\frac{1}{4}$ S 36

1918 ; raise a mound of

stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Asc. SW. slope 145 ft. to,

56.20 Head of a draw, course SW., asc. W. slope 400 ft. to,

80.00 Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in a large mound of stone, with 8 ft. base, on a solid limestone, ledge, (for standard cor. of Ts. 16 N., Rs. 68 and 69 E.,) with brass cap marked,