

RETRACEMENT OF A PORTION OF S. BOUNDARY OF T. 17 N., R. 68 E.

CHAINS The bearing of this $\frac{1}{2}$ mile is therefore N $89^{\circ} 55'$ E., and the dist. 39.98 chs.

From $\frac{1}{4}$ sec. cor. continue East.

79.98 Fall 4 lks S. of the cor. of secs. 4, 5, 32 and 33, hereinafter described.

The bearing of this $\frac{1}{2}$ mile is therefore N $89^{\circ} 57'$ E., and the dist., 40.00 chs.

From the cor. of secs. 4, 5, 32 and 33 East on retracement line bet. secs. 4 and 33

39.15 Fall 4 lks S. of $\frac{1}{4}$ sec. cor., hereinafter described.

The bearing of this $\frac{1}{2}$ mile is therefore N $89^{\circ} 57'$ E., and the dist. 39.15 chs.

SURVEY OF E. BOUNDARY OF T. 17 N., R. 68 E.

I begin at the cor. of Ts. 17 and 18 N., Rs. 68 and 69 E., marked and witnessed as described by the Surveyor General.

South bet. secs. 1 and 6

Over mountainous land, through scattering timber. Ascend.

9.55 Spur, 130 ft. above cor., projects E., desc. SW. slope.

19.35 Head of ravine, 95 ft. below spur, drains E., ascend.

23.00 Rocky spur, 55 ft. above ravine, projects E., desc. S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 23 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
 S1 | S6
 1920

Cedar, 8 ins. dia., bears S $69^{\circ} 15'$ E., 43 lks. dist., marked $\frac{1}{4}$ S6BT.

Cedar, 8 ins. dia., bears S 66° W., 88 lks. dist., marked $\frac{1}{4}$ S1BT.

50.70 Draw, 430 ft. below spur, drains E., trail. Asc. N. slope.

58.80 Spur, 105 ft. above draw, projects 5 chs. E., desc. S. slope.

65.40 Draw, 70 ft. below spur, drains NE., asc. N. slope.