


SURVEY OF E. BOUNDARY OF T. 17 N., R. 68 E.

CHAINS

the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Descend SW. slope.

46.00 Small spring, bears about 1 ch. W.

49.50 Intersect small spring.

49.70 Draw, 195 ft. below $\frac{1}{4}$ sec. cor., drains W., Asc. N. slope.

57.20 Rocky spur, 190 ft. above draw, projects W. about 10 chs.


Desc. along W. slope.

64.70 Draw, 130 ft. below spur, drains W., asc. NW. slope.

73.70 Spur. 235 ft. above draw, projects about 15 chs, W., desc. along SW. slope.

79.60 Draw, 20 ft. below spur, drains W., asc. N. slope 25 ft. to cor.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., on solid rock, supported by a mound of stone, for the cor. of secs. 25, 30, 31 and 36, with brass cap marked



Pine, 18 ins. dia., bears S $29^{\circ} 30'$ E., 59 lks. dist., marked T17NR69ES31BT.

Pine, 14 ins. dia., bears S $1^{\circ} 45'$ W., 94 lks. dist., marked T17NR68ES36BT.

No other trees available.

Land, mountainous.

Soil, rocky.

Timber, mt. mahogany, fir, and pine.

Undergrowth, sage.

South bet. secs. 31 and 36

Over rough mountainous land through scattering timber.

Asc. steep N. slope.

See map