

28. Retracement of the west boundary of T.9 N., R.28 E.

Chains	is N.0°09'W., and the distance is 39.92 chains.

	From the cor. of secs. 1, 6, 7 and 12.
	North on the west bdy. of sec. 6.
39.92	Fall 11 lks. E., to the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, hereinafter described. The course of this half mile is N.0°09'W., and the distance is 39.92 chains.
	From the $\frac{1}{4}$ sec. cor., North, on the west bdy. of sec. 6., with continuous chaining.
80.36	Fall 3 lks. West of the cor. of Ts. 9 and 10 N., Rs. 27 and 28 E., hereinafter described. The course of this half mile is N.0°03'E., and the distance is 40.44 chs.

	Dependent Resurvey of the south boundary of T.9 N., R.28 E.
	From the reconstructed cor. of Ts. 8 and 9 N., Rs. 28 and 29 E., described in Book A containing the field notes of the Resurvey of a portion of the South boundary of T.9 N., R.29 E.
	Thence on dependent resurvey, S.89°47'W., on the south boundary of sec. 36.
	Asc. 288 ft. over steep NE. slope, covered with sage brush.
10.80	Spur, slopes NE. Asc. 28 ft.
19.10	Main ridge of Walker River range, bears N. and S. Asc. 50 ft.
25.20	Commence desc. of steep SW. slope, 667 ft.
40.00	The old $\frac{1}{4}$ sec. cor. for sec. 1 and 36, which is a stone 14 x 10 x 8 ins. above ground, marked and witnessed as described by the Surveyor General, I reconstruct this cor. as follows: Set iron post, 3 ft. long, 1 in. in diam., 12 ins. in the ground, supported by mound of stone, 2 ft. base, 1½ ft. high, for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, with brass cap marked

$\frac{1}{4}$ S 36

S 1