

Chains	From the cor. for secs. 31 and 32, on S.bdy. of Tp.						
	N.0°1'E., between secs. 31 and 32.						
	Desc. 123 ft. over rocky NE. slope.						
8.61	Spring, running water 1 in. deep, 1 lks.wide, course E.						
	Asc. 279 ft. over SE. slope.						
13.00	Rocky spur, slopes SE.						
30.60	Main ridge between Squaw creek and Dutch creek, bears NE. and SW.						
	Desc. 1574 ft. over N. slope.						
40.00	Set iron post, 3 ft. long, 1 in. in dia., 12 ins. in the ground, supported by mound of stone, 2 ft. base, 1½ ft. high, for the ¼ sec. cor., with brass cap marked						
	$\frac{1}{4}$ S 31 S 32 1919						
	and raise mound of stone, 3 ft. base, 2 ft. high, W. of the cor.						
	Enter heavy timber, bears NW. and SE.						
80.00	Set iron post, 3 ft. long, 2 ins. in dia., 12 ins. in the ground, supported by mound of stone, 2 ft. base, 1½ ft. high, for the cor. of secs. 29, 30, 31 and 32, with brass cap marked.						
	<table border="1"> <tr> <td>T 9 N</td><td>R 29 E</td></tr> <tr> <td>S 30</td><td>S 29</td></tr> <tr> <td>S 31</td><td>S 32</td></tr> </table> 1919	T 9 N	R 29 E	S 30	S 29	S 31	S 32
T 9 N	R 29 E						
S 30	S 29						
S 31	S 32						
	from which						
	A pinion, 8 ins. diam., bears N.1°45'E., 57 lks. dist., marked T 9 N R 29 E S 29 B T.						
	A pinion, 10 ins. diam., bears S.28½°E., 91 lks. dist., marked T 9 N R 29 E S 32 B T.						
	A pinion, 12 ins. diam., bears S.27¾°W., 99 lks. dist., marked T 9 N R 29 E S 31 B T.						
	A pinion, 10 ins. diam., bears N.39½°W., 43 lks. dist., marked T 9 N R 29 E S 30 B T.						
	Land, mountainous; Soil, rocky, 3rd. rate; Timber, pinion and juniper; Undergrowth, sage and deer brush.						