Independent Resurvey of the W. boundary of T.42 N., R.51 E.

Chains 26.60 Telephone line, bears NW. and SE.

34.90 Ravine, course NW. Asc. 62 ft. over SW. slope.

37.00 From this point, a spring, bears S.70°E.,1.50 chs. dist.

40.00 Set iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground, surrounded by mound of stone, 2 ft. base, 1 ft. high, for the \(\frac{1}{4}\) sec. cor., with brass cap marked

$$\begin{bmatrix} \frac{1}{4} \\ 5 \end{bmatrix}$$
 $\begin{bmatrix} 1 \\ 5 \end{bmatrix}$ $\begin{bmatrix} 1 \\ 1919 \end{bmatrix}$

and raise mound of stone, 2 ft. base, 1 ft. high, W. of the cor.

57.70 Spur, slopes NW. Thence along NE. slope.

76.57 At proportionate distance.

Set iron post, 3 ft. long, 3 ins. in diam., 12 ins. in the ground, to bed rock, surrounded by amound of stone 3 ft. base, 12 ft. high, for the cor. of secs. 7 and 18, only, with brass cap marked

and raise mound of stone, 2 ft. base, $l^{\frac{1}{2}}$ ft. high, E. of the cor.

Land, mountainous; Soil, rocky, 3rd. rate; Timber, none; Undergrowth, sage brush.

-182-1442-144-144-1200

Dependent Resurvey of the N. boundary of T.41 N., R.51 E.

At the point, the position heretofore determined by double proportion of measurement afforthe cor. of Ts.

41 and 42 N., Rs. 51 and 52 E., set iron post, 3 ft.

long, 3 ins. in diam., 24 ins. in the ground, with brass cap marked