

INVESTIGATION SURVEY, GROUP 69, NEVADA.

Std. cor. of secs. 33 and 34. An iron post, 3 ins. diam. 12 ins. above ground, mkd and witnessed as described by the surveyor general.

Std. $\frac{1}{4}$ Sec. 34. An iron post, 1 in. diam., 15 ins. above ground, mkd and witnessed as described by the surveyor general.

Std. cor. of secs. 34 and 35.
By Haigh and Harris in 1914.
An iron post, 3 ins. diam., 12 ins. above ground, mkd and witnessed as described by the surveyor general.

By Criss in 1901.
Basalt rock, 22x15x12 ins., mkd SC on N. face, 2 grooves East and 4 grooves West, set in a mound of stone.

Std. $\frac{1}{4}$ Sec. 35. A mound of stone with a quartzite rock, 16x8x8 ins. in center, no marks discernible. This is undoubtedly the corner established by Deputy Maxson in 1893. No trace of the Criss $\frac{1}{4}$ cor.

Std. cor. of secs. 35 and 36.
By Maxson in 1893.
Quartzite stone, 4x10x15 ins. in a mound of stone, marked 5 grooves on West, no other marks discernible.

By Criss in 1901.
A mound of stone with a wooden post, 2x4 ins, by 4 ft. in center with the words "Section Corner" in blue pencil marks on one side. This corner on very steep hillside. Very probable that the Criss section corner has rolled down the slope.

Std. $\frac{1}{4}$ Sec. 36.
By Maxson in 1893.
Basalt stone. 1x5x5 ins. above ground, firmly set, mkd $\frac{1}{4}$ on NW face, surrounded by mound of stone.

By Criss in 1901.
Basalt stone, 15x10x4 ins. in mound of stone, mkd " $\frac{1}{4}$ SC" on N. face.

Std. cor. of Ts. 32 N., Rs. 33 and 34 E. Granite rock, 24x10x8 ins. in mound of stone, mkd SC and 6 notches on N. face, 6 notches on E. and W. faces. Diligent search was made in this vicinity for additional corners referring to T. 32 N., Rs. 33 and 34 E.

$\frac{1}{4}$ sec. cor. of secs. 33 and 34. An iron post, 1 in. diam., 12 ins. above ground, mkd and witnessed as described by the surveyor general.