

## RETRACEMENT OF THE BOUNDARIES OF SECTION 1, T. 31 N., R. 33 E.

## CHAINS

with 1 groove on N. face and 5 grooves on S. face.  
From this cor.

Cor. No. 4, "Humboldt No.2" Lode, M.S. No. 4195,  
bears N.21°52'W., 3.54 chs. distant.

Cor. of secs. 1 and 12, as established by Deputy  
Surveyor F.H.Criss in 1901, which is a rhyolite  
rock, 20x12x6 ins., set in a mound of stone, mkd.  
with 1 groove on N. face and 5 grooves on S. face,  
bears N.47°27'E., 3.78 chs. distant.

Land, mountainous.

Soil, rocky; 3rd to 4th rate.

Undergrowth, sagebrush, service-berry.

No timber.

From the 1893 cor. of secs. 1 and 12.  
N. 1°26'E., on true line, along E. bdy. of sec. 1.

Over mountainous land thru dense undergrowth. Over  
gradual NW. slope.

3.26 Intersect "Humboldt No.2" Lode, M.S. No. 4195,  
S.88°45'E., 1.40 chs. distant from Cor. No.4.  
Desc. N. slope.

7.10 Old road, bears E. and W., desc. 580 ft. over NE. slope  
thru heavy juniper timber, bears E. and W.

21.60 Draw, drains NE., along steep E. slope, leave heavy  
timber, bears NE. and SW., continue thru scattering  
juniper timber.

24.80 Trail, bears NE. and SW.

28.00 40 ft. below draw, slope changes to abrupt NE., desc.  
130 ft.

34.00 Foot of mountainous slope, bears NW. and SE., over  
bottom land, slight NW. slope.

38.50 Humboldt Creek, dry bed, course NW.

39.00 Ruins of old stone wall, bears NW. and SE.

39.29 The re-determined point for the  $\frac{1}{4}$  sec. cor. of sec. 1,  
from which Cor. No.1, "Humboldt Chief Lode", M.S.  
No. 4293, bears S. 30°55'E., 8.02 chs. distant.