

Subdivisions of T. 11 N., R. 70 E.

Chains. From the standard cor. of secs. 31 and 32, home S. Bdy. of Township heretofore described.

N. $0^{\circ} 01'$ E., bet. secs. 31 and 32.

17.60 Dry wash, 169 ft. below sec. cor., course S.E.

20.40 Top of spur, 14 ft. above wash, bears S.E.

31.80 Dry wash, 31 ft. below spur, course S.E.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 18 ins. in the ground, supported by a mound of stone, 3 ft. base, 18 ins. high, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S31		S32
	1921	

40 ft. above wash,

from which

a pinion pine 4 ins. in dia., bears S. $79\frac{1}{2}^{\circ}$ E., 134 lks. dist., marked $\frac{1}{4}$ S 32 B T

a pinion pine 3 ins. in dia., bears N. 80° W., 80 lks. dist., marked $\frac{1}{4}$ S 31 B T

47.40 Dry wash, 41 ft. above $\frac{1}{4}$ sec. cor., course S.E.

49.90 Top of spur, 20 ft. above wash, bears S.E.

58.40 Dry wash, 18 ft. below spur, course E.

59.70 Top of spur, 16 ft. above wash, bears E.

71.70 Dry wash, 57 ft. below spur, course S.E.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 10 ins. in the ground, supported by a mound of stone, 3 ft. base, 26 ins. high, for the cor. of secs. 29, 30, 31 and 32, with brass cap mkd.

T11N		R70E
S30		S29
S31		S32
	1921	

31 ft. above wash,

from which

a cedar 6 ins. in dia., bears N. 34° E., 51 lks. dist., marked T 11 N R 70 E S 29 B T

a pinion pine 6 ins. in dia., bears S. $37\frac{1}{4}^{\circ}$ E., 25 lks. dist., marked T 11 N R 70 E S 32 B T

a pinion pine 8 ins. in dia., bears S. $37\frac{1}{4}^{\circ}$ W., 11 lks. dist., marked T 11 N R 70 E S 31 B T