

Dependent Resurvey of the S. Bdy. of T. 13 N., R. 70 E.

Chains. Sec. 31, with brass cap mkd.

$\frac{1}{4}$  S31

1921

841 ft. below spur.

From the  $\frac{1}{4}$  cor. for Sec. 31,

S.  $88^{\circ} 46'$  E., on a true line, on S. Bdy. of Sec. 31.

42.02 An easting of 40.00 chs. from the true point for the cor. of T. 12 N., R's. 69 and 70 E., determined by previous retracements.

Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in the ground, in a mound of stone, for the  $\frac{1}{4}$  sec. cor. of sec. 3, with brass cap mkd.

$\frac{1}{4}$  S5

1921

30 ft. below  $\frac{1}{4}$  sec. cor. of sec. 31; desc. abrupt N.E. slope.

62.00 Head of dry wash, 200 ft. below  $\frac{1}{4}$  sec. cor., bears N.E.

78.80 Top of spur, 638 ft. above wash, bears N.E.

79.85 A easting of 40.05 chs. from the old  $\frac{1}{4}$  sec. cor. for sec. 31, which is the proportionate dist. for the cor. of secs. 31 and 32,

set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 31 and 32, with brass cap mkd.

T13N	R70E
S31	S32

T12N R70E  
S6  
1921

from which

a mahogany 6 ins. in dia., bears N.  $64\frac{1}{2}^{\circ}$  E., 22 lks. dist., marked T 13 N R 70 E S 32 B T

a mahogany 6 ins. in dia., bears N.  $60\frac{1}{2}^{\circ}$  W., 50 lks. dist., marked T 13 N R 70 E S 31 B T

Land, rough mountainous, with numerous outcroppings of quartzite formation. Undergrowth, scattering sage. Timber, pinion pine, cedar, mahogany and spruce.