

Independent Resurvey of the W. Bdy. of T. 12 N., R. 70 E.

Chains.

WC
T12N
R69E | R70E
S1 | S6
S12 | S7
1921

from which

a pinon pine 6 ins. in dia., bears N. 83° E., 15 lks.

dist., marked W C T 12 N R 70 E S 6 B T

a pinion pine 8 ins. in dia., bears S. 2½° E., 49 lks.

dist., marked W C T 12 N R 70 E S 7 B T

a pinon pine 6 ins. in dia., bears S. 85½° W., 19 lks.

dist., marked W C T 12 N R 69 E S 12 B T

a pinon pine 8 ins. in dia., bears N. 48½° W., 49 lks.

dist., marked W C T 12 N R 69 E S 1 B T

80.00

True point for sec. cor. falls on limestone ledge.

Impracticable to set cor. Mark a cross on ledge for the true point for the cor. of secs. 1, 6, 7 and 12.

Land, rough mountainous. Soil, sandy and rocky; 4th rate. Undergrowth, shadscale and sage. Timber, pinion pine, cedar and mahogany.

North, on a true line, bet. secs. 1 and 6.

Ascend abrupt S.E. slope over rough mountainous land, through dense pinon pine and mahogany.

6.00

Top of rocky spur, 117 ft. above sec. cor., bears E.

13.80

Dry wash, 57 ft. below spur, course S.E.

Leave dense pinon pine and mahogany; bears N.W. and S.E.; enter scattering pinon pine and mahogany.

19.60

Top of spur, 93 ft. above wash, bears E.

23.70

Dry wash, 44 ft. below spur, course S.E.

30.90

Top of spur, 63 ft. above wash, bears S.E.

35.00

Dry wash, 45 ft. below spur, course S.E.; enter dense mahogany, bears N.W. and S.E.

40.00

Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the ¼ sec. cor., with brass cap mkd,

S1 | S6
|
1921