

Independent Resurvey of the W. Bdy. of T. 12 N., R. 70 E.

Chains. 95 ft. above draw,
 from which
 a pinon pine 5 ins. in dia., bears N. 25° E., 58 lks. dist., marked $\frac{1}{4}$ S 6 B T
 a pinon pine 8 ins. in dia., bears N. $64\frac{1}{2}^{\circ}$ W., 35 lks. dist., marked $\frac{1}{4}$ S 1 B T
 75.20 Top of Ridge, 566 ft. above $\frac{1}{4}$ sec. cor., bears E. for about 20.00 chs., thence S.E.; from W.
 78.57 Intersect the S. Bdy. of T. 13 N., R. 70 E., N. $88^{\circ} 44'$ W., 2.01 chs. dist., to the cor. of T. 13 N., R's. 69 and 70 E., hereinbefore described.
 Set an iron post, 3 ft. long, 3 ins. in dia., 15 ins. in slide rock, in a mound of stone, 8 ft. base, 24 ins. high, for the cor. of T. 12 N., R's. 69 and 70 E., with brass cap mkd.

T13N R70E

S31

S1 | S6

R69E R70E

T12N

1921

250 ft. below ridge,

from which

a spruce 10 ins. in dia., bears S. 44° E., 64 lks. dist., marked T 12 N R 70 E S 6 B T

a spruce 6 ins. in dia., bears S. $72\frac{1}{2}^{\circ}$ W., 25 lks. dist., marked T 12 N R 69 E S 1 B T

Land, rough mountainous with many exposed outcroppings of limestone and quartzite formation. Soil, rocky and sandy; 4th rate. Timber, pinon pine, mahogany and cedar.

Subdivisions of T. 12 N., R. 70 E.

From the cor. of secs. 5, 6, 31 and 32, T's. 11 and 12 N., R. 70 E., described in the field notes of T. 11 N., R. 70 E.,

N. $0^{\circ} 01'$ E., on a true line, bet. secs. 31 and 32.

Ascend S.E. slope over rough mountainous land, through