

Chains

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

57.00 Dim road, bears NW. and SE.

71.65 Well traveled road, bears NE. and SW.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for cor. of secs. 13 and 24, with brass cap mkd.

T28N
S13
S24
R40E
1921

dig pits, 18x18x12 ins. NW. and SW. 3 ft. dist. from cor. Land, level. Soil, light sandy gravel clay loam, medium texture dry. Undergrowth, sagebrush and very little grass. Drainage NE.

North, on E. Bdy. of sec. 13.

Over nearly level land, draining NE., through dense undergrowth.

3.94 Intersect the original cor. of secs. 13, 18, 19 and 24, established by Hatch, Eaton and Smyles under Contract No. 51 in 1872, which I find to be a granite stone, 4x6x12 ins. above the ground, firmly set in a mound of stone, mkd. with 3 grooves on N. and S. faces. I now reconstruct this cor. as follows: Alongside, Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for cor. of secs. 18 and 19, with brass cap mkd.

T28N
S18
S19
R41E
1921

dig pits, 18x18x12 ins. NE. and SE., 3 ft. dist. from cor. Thence on a dependent resurvey of the E. Bdy. T. 28 N., R. 40 E. and bet. secs. 13 and 18, continuing with line and measurement.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for ¼ cor. of sec. 13, with brass cap mkd.

¼
S13
1921