

RETRACEMENT 4TH. STANDARD PARALLEL NORTH, RANGE 45 EAST

CHAINS

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

Thence

West, on retracement line along S. bdy. sec. 36

40.38 Fall 4 lks. N. of the standard $\frac{1}{4}$ sec. cor. hereinafter described.

The bearing of this $\frac{1}{2}$ mile is S.89°57'W., and the distance is 40.38 chs.

From standard $\frac{1}{4}$ sec. cor., continue

West

80.95 Fall 5 lks. N. of the standard cor. of secs. 35 and 36 hereinafter described.

The bearing of this $\frac{1}{2}$ mile is S.89°56'W., and the distance is 40.57 chs.

From the standard cor. of secs. 35 and 36.

West, on retracement line along S. bdy. sec. 35

40.55 Fall 5 lks. N. of the standard $\frac{1}{4}$ sec. cor. hereinafter described.

The bearing of this $\frac{1}{2}$ mile is S.89°56'W., and the distance is 40.55 chs.

From standard $\frac{1}{4}$ sec. cor., continue

West.

70.90 Fall 3 lks. N. of the standard cor. of secs. 34 and 35 hereinafter described.

The bearing of this $\frac{1}{2}$ mile is S.89°57'W., and the distance is 30.35 chs.

From the standard cor. of secs. 34 and 35.

West, on retracement line along S. bdy. sec. 34.

40.58 Fall 6 lks. N. of the standard $\frac{1}{4}$ sec. cor. hereinafter described.

The bearing of this $\frac{1}{2}$ mile is S.89°55'W., and the distance is 40.58 chs.

From standard $\frac{1}{4}$ sec. cor., continue

West.