

DEPENDENT RESURVEY 4TH STANDARD PARALLEL NORTH, RANE 45 EAST.

CHAINS

SC  
 $\frac{1}{4}$  S31  
-----  
1920

49.38 Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
No trace of the old standard  $\frac{1}{4}$  sec. cor. can be found.  
Westing of 40.00 chs. from the closing cor. of secs. 5  
and 6, T.20 N., R.45 E.  
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in  
a large mound of stone on solid rock for  $\frac{1}{4}$  sec. cor.  
N. bdy. sec. 6, with brass cap marked.

$\frac{1}{4}$  S6  
1920

51.00 Ridge, 110 ft. above standard  $\frac{1}{4}$  sec. cor., bears N. and  
SE.; descend 405 ft. to

79.12 The standard cor. of T.21 N., Rs 44 and 45 E., which is  
an iron post, 3 ins. in dia., firmly set in the ground,  
and marked and witnessed as described by the surveyor  
general.

Land, mountainous; drainage SE. Soil, gravelly and rocky;  
granite formation. No timber. Undergrowth, dense sagebrush  
and scattering yellow top.

NOTE:-For the sake of clearness the quarter sec. cors. for  
subdivisions in T. 20 N., R. 45 E., are inserted at this  
place in the field notes, altho their positions were  
subsequently determined.

RETRACEMENT AND DEPENDENT

RESURVEY OF THE WEST BOUNDARY OF T.20 N., R.45 E.

I begin at the cor. of Tps. 19 and 20 N., Rs. 44 and 45  
E., which is a quartzite stone, 10 x 8 x 7 ins. above  
ground, firmly set, and marked and witnessed as des-  
cribed by the surveyor general.

Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in  
the ground alongside old cor. for cor. of Tps. 19 and  
20 N., Rs. 44 and 45 E., with brass cap marked

|      |      |
|------|------|
| T20N |      |
| R44E | R45E |
| S36  | S31  |
| S1   | S6   |
| T19N |      |

1920