

DEPENDENT RESURVEY AND SURVEY OF THE SOUTH BOUNDARY OF T.20 N., R.45 E.

CHAINS

3 ft. long, 2 ins. in dia., 24 ins. in the ground for cor. of secs. 5 and 6, T.19 N., R.45 E., with brass cap marked

S6	S5
T19N	R45E

1920

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

Land, rolling; general S. drainage.

Soil, sandy on west half mile, brown clay on east half mile; granite formation.

No timber.

Undergrowth, dense sage, scattering yellow top and rabbit brush.

SURVEY OF SOUTH BOUNDARY OF T. 20 N., R. 45 EAST

From the cor. of secs. 5 and 6, T.19 N., R.45 E.

East, on true line bet. secs. 5 and 32.

Over rolling mountainous land through very scattering cedar and pinon timber and undergrowth of sage, yellow top and scrub mahogany. Ascend SW. slope.

10.40 Top of ascent, 150 ft. above cor.; descend.

21.75 Draw, 105 ft. below top of ascent, drains N.10°W.; ascend.

38.17 Easting of 40.00 chs. from cor. of secs. 31 and 32.

Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in the ground on solid rock and 16 ins. in a mound of stone for $\frac{1}{2}$ sec. cor., with brass cap marked

$\frac{1}{2}$ S32

1920

41.75 Spur, 100 ft. above draw, projects N.; gradually descend.

61.15 Old road, bears N. and S.

78.17 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground for cor. of secs. 32 and 33, T.20 N., R.45 E., with brass cap marked

T20N	R45E
S32	S33

1920

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.