

## SUBDIVISION OF T.20 N., R.45 E.

## CHAINS

- Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.  
 67.90 Telephone line, bears NE. and SW.  
 80.01 The cor. of secs. 2, 3, 10 and 11.  
 Land, rolling; general NE. drainage.  
 Soil, sandy and gravelly; granite formation.  
 No timber.  
 Undergrowth, dense sagebrush and scattering yellow top.

- N.  $0^{\circ}01'W.$ , on true line bet. secs. 2 and 3.  
 Gradually descend over rolling mountainous land through  
 undergrowth of sagebrush and yellow top.  
 24.10 Draw, 135 ft. below cor., drains N.  $70^{\circ}E.$ ; ascend.  
 27.65 Spur, 40 ft. above draw, projects N.  $70^{\circ}E.$ ; descend.  
 36.70 Draw, 60 ft. below spur, drains NE.; ascend 30 ft. to  
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in  
 the ground for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
 S3 | S2

1920

- Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
 Continue ascent.  
 44.15 Spur, 20 ft. above  $\frac{1}{4}$  sec. cor., bears NE. and SW.; road  
 from Austin, Nevada to Grass Valley Ranch, bears NE.  
 and SW.; descend.  
 60.75 Draw, 140 ft. below spur, drains NE.; ascend.  
 78.05 Spur, 110 ft. above draw, projects E.; descend.  
 88.70 Draw, 35 ft. below spur, drains E.; ascend.  
 97.26 Intersect 4th. Standard Parallel North, 12.28 chs.  
 S.  $89^{\circ}55'W.$ , of the standard cor. of secs. 34 and 35  
 heretofore described.  
 At point of intersection,  
 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins.  
 in the ground for closing cor. of secs. 2 and 3, with  
 brass cap marked

T21NR45E  
 S34  
 S3 | S2  
 T20N | R45E  
 CC  
 1920