

SUBDIVISION OF T.20 N., R.45 E.

CHAINS	and SW. Road forks NW. to Callahan Ranch about 3 chs. NE.
75.05	Low spur, 90 ft. above swale, projects NE.; gradually descend.
79.96	The cor. of secs. 3, 4, 9 and 10. Land, rolling mountainous; general drainage NE. Soil, gravelly and sandy loam; granite formation. No timber. Undergrowth, dense sagebrush and scattering yellow top.
	N.0°02'W., on true line bet. secs. 3 and 4. Descend over rolling mountainous land through undergrowth of sagebrush and yellow top.
1.90	Swale, drains N.60°E.; ascend.
8.00	Spur, 35 ft. above swale, projects E.; descend.
14.65	Draw, 45 ft. below spur, drains N.80°E.; ascend.
27.10	Low spur, 10 ft. above draw, projects E.; descend.
40.00	Head of swale, 40 ft. below spur, drains E. Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked
	<div style="text-align: center;"> $\frac{1}{4}$ S4 S3 1920 </div>
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Gradually ascend.
69.20	Point of spur, breaks to gentle slope, bears E. and W.; descend.
83.80	Enter scattering pinon timber, bears E. and W.
95.40	Draw, 61 ft. below spur, drains SE.; ascend.
96.96	Intersect 4th. Standard Parallel North, 11.10 chs. S.89° 43'W., of the standard cor. of secs. 33 and 34 heretofore described. At point of intersection, Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground for closing cor. of secs. 3 and 4, with brass cap marked