


SUBDIVISION OF T.20 N.,R.45 E.

CHAINS

32.80 Draw, 520 ft. below cor., drains E.; ascend.

40.00 On SE. slope 165 ft. above draw.

Set an iron post, 3 ft.long, 1 in. in dia., 26 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap marked



Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Continue ascent.

50.00 Spur, 165 ft. above $\frac{1}{4}$ sec. cor., projects E.; descend.


84.75 Draw, 570 ft. below spur, drains E.; ascend.

91.85 Spur, 90 ft. above draw, projects E.; descend.

97.28 Intersect 4th. Standard Parallel North, 9.38 chs. S.89° 54'W. of the standard cor. of secs. 31 and 32 heretofore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground for closing cor. of secs. 5 and 6, with brass cap marked



Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

Cor. stands on S. edge of draw.

Land, rolling mountains; general E. drainage.

Soil, sandy and rocky; granite formation.

No timber.

Undergrowth, dense sagebrush and scattering yellow top.