

RETRACEMENT OF A PORTION OF SUBDIVISIONS OF T. 18 N., R. 49 E.

CHAINS	West	
40.00	Fall 20 lks. S. of proportionate point for the cor. of secs., 25 and 36, hereinafter established.  The bearing of this $\frac{1}{2}$ mile is therefore S 89° 43' E., and the dist. 40.00 chs.	
	V	
	<p><u>DEPENDENT RESURVEY OF E. BOUNDARY OF T. 18 N., R. 49 E.</u></p> <p>I begin at the closing cor. of T. 18 N., Rs. 49 and 50 E., which is a granite rock 18X10X7 ins., firmly set in the ground, marked and witnessed as described by the Surveyor General</p> <p>Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground, alongside old cor., for the <del>closing</del> cor. of T. 18 N., Rs. 49 and 50 E., with brass cap marked</p> <div><div>T19N R50E</div><div>S31</div><div>S1   S6</div><div>R49E   R50E</div><div>T18N</div><div>1920</div></div> <p>The cor. of T. 19 N., Rs. 49 and 50 E., bears West 7.72 chs. dist.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. Thence S 1° 14' E., on resurvey line bet. secs. 1 and 6 Over gently rolling land</p> <p>50.81 The old <math>\frac{1}{4}</math> sec. cor., which is a pine post, firmly set in the ground, marked and witnessed as described by the Surveyor General</p> <p>Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor. sec. 6, alongside old cor., with brass cap marked</p> <div><div><math>\frac{1}{4}</math></div><div> </div><div>S6</div><div>1920</div></div> <p>Raise a mound of stone, 3 ft. base, 1<math>\frac{1}{2}</math> ft. high, E. of cor. Thence S 0° 18' E., with continuous measurement</p> <p>51.04 Northing of 40.00 chs. from the cor. of secs. 1 and 12, hereinafter described</p>	