

DEPENDENT RESURVEY OF E. BOUNDARY OF T. 18 N., R. 49 E.

CHAINS

Thence

S 0° 24' E., with continuous measurement.

Descend


53.47 Draw, 30 ft. below  $\frac{1}{4}$  sec. cor., drains E., asc.

58.70 Spur, 30 ft. above draw, projects E., desc.

66.74 Hollow, 50 ft. below spur, drains E., slight ascent

77.00 Road, bears E. and W.

80.24 The cor. of secs. 25, 30, 31 and 36, which is a volcanic rock, firmly set in a mound of stone, marked and witnessed as described by the Surveyor General  
Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground, alongside old cor., for the cor. of secs. 25, 30, 31 and 36, with brass cap marked



Raise a mound of stone, 3 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.  
Land, rolling bench. Soil, rocky sand. Timber, cedar and pinon. Undergrowth, sage. General drainage, E.

S 0° 04' E., on resurvey line bet. secs. 31 and 36  
Slight ascent over rolling land.

13.79 Spur, 15 ft. above cor., projects E., desc.

18.17 Draw, 30 ft. below spur, drains E., asc.

25.69 Spur, 90 ft. above draw, projects E., asc. across head of draw, draining E.

38.74 Spur, 40 ft. above spur, projects E., desc.

39.79 The old  $\frac{1}{4}$  sec. cor., which is a volcanic rock, firmly set in a mound of stone, marked and witnessed as described by the Surveyor General  
Set an iron post, 3 ft. long, 1 in. in dia., on solid rock over marked stone, surrounded by a mound of stone, alongside old cor., for  $\frac{1}{4}$  sec. cor., with brass cap marked