

## DEPENDENT RESURVEY OF PORTION OF SUBDIVISIONS OF T. 18 N., R. 49 E.

CHAINS

Thence

N 88° 33' E., with continuous measurement

79.87 The cor. of secs. 13, 18, 19 and 24, hereinbefore

described

Land, gently rolling. Soil, gravelly. Timber, cedar and  
pinon. Undergrowth, sage. General drainage, E.

## INDEPENDENT RESURVEY OF PORTION OF S. BOUNDARY OF T. 18 N., R. 49 E.

From the cor. of secs. 35 and 36 on the S. bdy. of the  
tpw., hereinbefore described.West, on random line along S. bdy. of tpw., setting  $\frac{1}{4}$  sec.

and sec. cors. at regular intervals of 40.00 and 80.00,

and at

415.22 Intersect W. bdy. of the tpw., 17.44 chs. North of the  $\frac{1}{4}$   
sec. cor. sec. 36, T. 18 N., R. 48 E., which is a 1 in.  
iron post, firmly set in the ground, marked and witnessed  
as described by the Surveyor GeneralSet an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in  
the ground for the cor. of tps. 17 and 18 N., R. 49 E.,  
with brass cap marked

T18N R49E

1921

Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

From the cor. of secs. 35 and 36

West, on resurvey line on S. bdy. sec. 35.

Asc. E. slope.

1.18 Spur, 20 ft. above cor., projects N., desc. W. slope

4.43 Head of draw, 105 ft. below spur, drains N., asc. E. slope.

34.00 Ridge, 425 ft. above draw, bears N. and S., desc.

55.22 Easting of 360.00 chs. from W. bdy. of tp.

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor. sec. 35, with brass cap  
marked