

## INDEPENDENT RESURVEY OF PORTION OF S. BOUNDARY OF T. 18 N., R. 49 E.

CHAINS

Land, mountainous. Soil, rocky. Timber, pinon.  
Undergrowth, sage and aspen. General drainage NW.

West, on resurvey line on S. bdy. of sec. 31

Asc. steep E. slope.

10.50 Ridge, 305 ft. above sec. cor., bears N. and S.

Descend steep NW. slope.

29.70 Creek, 235 ft. below ridge, course NW., good water, 1 lk.

wide, 1 in. deep, asc. NE. slope, 25 ft.,

39.00 Desc. NW. slope 310 ft. to draw.

40.00 Easting of 40.00 chs. from W. bdy. of tp.

Set an iron post, 3 ft. long, 1 in. in dia., 16 ins. in  
the ground, over a marked stone, surrounded by a mound  
of stone, for  $\frac{1}{4}$  sec. cor. sec. 31, with brass cap  
marked

$\frac{1}{4}$ S31

1921

55.74 Seeping spring, bears S. 50 lks. dist., drains NW.

61.24 Draw, 310 ft. below descent, drains N., asc. steep SE.  
slope 440 ft. to cor.

80.00 The cor. of Tps. 17 and 18 N., R. 49 E., hereinbefore  
described.

Land, mountainous. Soil, rocky. Timber, pinon.

Undergrowth, sage and aspen. General drainage NW.

## RETRACEMENT AND SURVEY OF W. BOUNDARY OF T. 18 N., R. 49 E.

CHAINS

From the cor. of Tps. 17 and 18 N., R. 49 E.

North bet. secs. 31 and 36

22.78 The cor. of secs. 25 and 36, which is a 2 in. iron post,  
firmly set in the ground, marked and witnessed as  
described by the Surveyor General

40.00 Thence, on same line bet. secs. 25 and 31, with continuous  
measurement.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 6 ins. in  
the ground over a marked stone, surrounded by a mound  
of stone, for  $\frac{1}{4}$  sec. cor. sec. 31, with brass cap  
marked