

RETRACEMENT AND SURVEY OF N. BOUNDARY OF T. 18 N., R. 49 E.

CHAINS sec. 1, with brass cap marked

$\frac{1}{4}$ S1
 1920

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

78.67 The cor. of T. 19 N., Rs. 49 and 50 E., which is a 3 in. iron post, firmly set in the ground, marked and witnessed as described by the Surveyor General

Thence

East, on N. bdy. of sec. 1 with continuous measurement.

86.39 The closing cor. for. T. 18 N., Rs. 49 and 50 E., hereinbefore described.

SURVEY OF SUBDIVISIONS OF T. 18 N., R. 49 E.

From the cor. of secs. 31 and 32 on S. bdy. of tp., hereinbefore described.

N $0^{\circ} 01'$ E., bet. secs. 31 and 32

Asc. along SE. slope.

5.40 Rocky spur, 90 ft. above cor., projects E., Desc. NE. slope

18.74 Enter dense aspen thicket, bears NW. and SE.

22.18 Creek, 345 ft. below spur, course NW., 3 lks. wide, 2 ins. deep. Asc. along SW. slope, 185 ft. to $\frac{1}{4}$ sec. cor.

27.18 Leave thicket, bears NW. and SE.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in a mound of stone over a marked stone, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
 S31 | S32
 1921

Thence along W. slope

46.60 Spur, projects NW., desc. NW. slope.

54.40 Ravine, 215 ft. below spur, water 2 lks. wide, 2 ins. deep, course W. Asc. S. slope.

63.82 Ridge, 70 ft. above ravine, bears E. and W., thence along NW. slope with 40 ft. desc. to sec. cor.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 12 ins. in the ground over a marked stone, surrounded by a mound