

MEASUREMENTS.

All measurements are made with a Lallie 5-chain steel tape, compared with a Lufkin standard steel tape and found correct. All measurements are made on the slope, the vertical angle determined, and the slope measurements properly reduced to the true horizontal distances.

RETRACEMENT OF THE NORTH BOUNDARY OF T. 43 N., R. 53 E.

From the closing cor. of Ts. 43 and 44 N., R. 53 E., which is a granite stone, 24x12x4 ins., marked as described by the surveyor general and lying on surface of rocky hillside in remnants of scattered mound of stone To restore this cor., set an iron post, 3 ft. long, 3 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, with brass cap mkd:

T 44 N	
C S 31	
C S 6	R 53 E
T 43 N	

1920

and rebuild a mound of stone, 3 ft. base, 1½ ft. high, E. of cor.

Thence, East on retracement

- 65.95 No trace of orig. ¼ sec. cor.
- 105.73 Fall 35 lks. S. of the orig. cor. of secs. 5, 6, 31 and 32, hereinafter described. The course of this mile is S.89°49' W., and the proportionate lengths are 39.92 chs. for the E. ½ mile and 65.81 chs. for the W. ½ mile.

From the cor. of secs. 5, 6, 31 and 32,

East, on retracement,

- 39.87 Fall 21 lks. S. of the orig. ¼ sec. cor, hereinafter described. The course of this line is S.89°42' W., and the distance is 39.87 chs.

East, from ¼ sec. cor.

- 39.71 Fall 2 lks. S. of the orig. cor. of secs. 4, 5, 32 and 33, hereinafter described.