

DEPENDENT
RETRACEMENT AND RESURVEY OF PART OF THE WEST BOUNDARY
OF T. 46 N., R. 54 E.

CHAINS

sec. 31, T. 46 N., R. 54 E., being plainly visible,
Desc. 280 ft. over broken SW. slope. Thomas Stinton's
house bears S.38°W., 24.50 chs. distant.
telephone line at
43.30 Road and/base of slope, bears NW. and SE.
43.85 Cor. No. 14, H.E.S. No. 76, which is a basaltic stone,
ground,
8x10x10 ins. above/firmly set, mkd. and wit. as desc-
ribed by the Surveyor General.
59.81 A northing of 40 chs. from the SE. cor. of sec. 1,
Set an iron post, 3 ft. long, 1 in. diam., 36 ins. in
the ground, for $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass
cap mkd:

$$S \ 1 \ \frac{1}{4}$$
1921
and raise a mound of stone, 2 ft. base, 1 ft. high,
over top of post.
61.98 The SW. cor. of T.46 N., R.54E., hereinbefore described.

ers
Begin

SURVEY OF THE EAST BDY. OF T. 45 N., R. 53 E.
From the cor. of Tps. 44 and 45 N., Rs. 53 and 54 E.,
which is an iron post, 3 ins. diam., projecting 6 ins.
above ground, as set by me in 1920, and mkd. and wit.
as described in the Field Notes of T. 44 N., R. 53 E.
North, bet. secs. 31 and 36, in H.E.S. No. 54,
Along creek bottom thru dense willow thickets.
1.50 Trail Creek, 6 lks. wide, 4 ins. deep, flows NE.
8.40 Trail Creek, 8 lks. wide, 4 ins. deep, flows N.60°W.,
3 chs. thence northerly.
33.00 Trail Creek, 8 lks. wide, 3 ins. deep, flows N.20°E.
33.40 Leave creek bottom, bears N.15°E., and S.15°W., asc.
gradual SE. slope.
37.47 Wire fence, bears N.59°E. and S.59°W.
40.00 On E. slope, 40 ft. above creek,
Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in
the ground to solid rock, and 10 ins. in a mound of
stone, for $\frac{1}{4}$ sec. cor. of secs. 31 and 36, with brass

cap mkd:

$$S \ 36 \ S \ 31$$
1920