

SURVEY OF THE WEST BDY. OF T. 45 N., R. 53 E.

Chains

described in field notes of T 44 N R 53 E., Group 73, Book "A".

- 19.99 The restored cor. of Tps. 44 and 45 N., R 52 E., which is an iron post, 3 ins. diam., projecting 6 ins. above ground, firmly set, as established by me in 1920, and mkd. and wit. as described by the Surveyor General, in the field notes of T. 44 N., R. 53 E.

Thence, with continuous measurement.

North, on true line, along W. bdy. of sec. 31,

Asc. 230 ft. over SE. slope.

- 36.10 Ridge, bears N. 70°E. and W., leave dense undergrowth, enter scattering undergrowth and grasses. Desc. 80 ft. over NW. slope.

- 40.01 At 40.00 chs. northing from the SW. cor. of sec. 31, Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for cor. of sec. 31 only, with brass cap mkd:

1/4 S 31

1921

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, East of cor. No bearing trees within reasonable dist. Desc. 1165 ft. over NW. slope thru scattering undergrowth and dense grasses.

- 74.90 Enter heavy timber, bears E. and SW.

- 79.08 Trail, bears E. to Woodward's tunnel and NW. 4 chs. to site of Woodward's camp.

- 80.01 At 80.00 chs. northing from the SW. cor. of sec. 31, Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 30 and 31, with brass cap mkd:

T45N

R53E

S 30

1/4 S 31

1921