

Subdivision of T. 45 N., R. 53 E.

CHAINS

- and raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. From cor., the Old Std. $\frac{1}{2}$ sec. cor. of sec. 33, now destroyed, bears S. $54^{\circ}15'E.$, 3.30 chs. distant. No suitable bearing trees within reasonable distance.
- 41.00 Enter thicket of very dense undergrowth and scrub aspen timber, bears W. and SE., on top of spur ridge, bearing SE. and S. from NW. Desc. NE. slope.
- 53.90 Draw, 100 ft. below ridge, drains SE., leave aspen thickets, bear NW. and SE., asc. S. slope.
- 55.17 Road, bears N. $80^{\circ}W.$ and S. $80^{\circ}E.$
- 67.10 Spur, 100 ft. above draw, projects SE., asc. 40 ft. over broken SE. slope.
- 74.50 Draw, drains S. $15^{\circ}E.$, asc. 60 ft. over broken S. slope.
- 85.00 Low flat top of ridge, bears E. and W., desc. 50 ft. over broken NW. slope.
- 100.17 Intersect Ninth Standard Par. North, 1.10 chs. West of the Std. $\frac{1}{2}$ sec. cor. of sec. 34, which is an iron post, 1 in. diam., extending 12 ins. above the ground, firmly set, mkd. and wit. as described by the Surveyor General.
- At point of intersection,
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 3 and 4, with brass cap mkd.
- | | |
|------|------|
| T46N | R53E |
| S 34 | |
| S 4 | S 3 |
| T45N | R53E |
| CC | |
| 1921 | |
- and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
- Land, mountainous. General E. drainage.
- Soil, shallow gravelly and rocky loam, coarse texture, rocky subsoil, limestone formation, 3rd rate.
- Undergrowth, sagebrush, buck brush, service berry, willows, yellow top.
- Timber, aspen, water birch. Excellent grazing.