

RE-ESTABLISHMENT OF THE NORTHWEST TOWNSHIP CORNER FOR
T. 14 N., R. 70 E.

Chains



and rebuild mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
E. of cor.

Thence

North, on retracement, on W. bdy. of T. 14 N., R. 70 E.
searching for original corners at record distances
none of which were found.

120.00 No trace of original Tp. cor., set temp. cor.

The original cor. of secs. 4, 5, 32 and 33, on the
N. bdy. of T. 14 N., R. 70 E., is a cedar stake, with
squared edges, set in a mound of earth and witnessed
by pits. The scribe marks on corner are distinct on
two edges showing marks for secs. 4 and 33 but on the
other sides the marks are faint and unreadable.

Alongside of original stake, set an iron post, 3 ft.
long, 2 ins. diam., 24 ins. in the ground, with brass
cap mkd:

T 15 N	R 70 E
S 32	S 33
S 5	S 4
T 14 N	
1920	

renew the original pits.

Thence

West, on random line searching for original corners at
record distances, none of which were found.

157.00 No trace of Tp. cor., set temp. cor.

160.40 Intersect the projected W. bdy. of Tp., 4.21 chs. N.
of the first temp. Tp. cor.

Re-establishing the northwest township corner of T.14 N.
R.70E., at the intersection of cardinal offsets from
the temp. Tp. corners, by moving the first temp. cor.
3.40 chs. East, at which point, set an iron post, 3