

SURVEY OF THE THIRD STANDARD PARALLEL NORTH THRU RANGE 69 EAST.

Chains.

From the Std. cor. of T. 16 N., Rs. 68 and 69 E., which is an iron post, 3 fns. diam., firmly set and mkd and witnessed as described by the surveyor general.

Thence

East, on true line, along S. bdy. of T.16 N., R. 69 E., Desc. 540 ft. over rough NE. slope thru scattering undergrowth and timber.

26.50 Draw, drains N., asc. 140 ft. over rocky W. slope.

35.48 Spur, slopes N., desc. 175 ft. abruptly over rocky NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for Std. $\frac{1}{4}$ sec. cor. of sec. 31, with brass cap mkd:

S C
 $\frac{1}{4}$ S 31

1920

from which

A spruce, 12 ins. diam., bears N.73 $\frac{1}{2}$ °E., 106 lks dist., mkd. SC $\frac{1}{4}$ S31 SC BT
A mahogany, 5 ins. diam., bears N.43 $\frac{1}{2}$ °W., 64 lks. dist., mkd. SC $\frac{1}{4}$ S31 SC BT

40.75 Small draw, drains N., asc. 30 ft. over W. slope.

47.50 Top of ascent, slope changes to abrupt E., desc. 470 ft.

68.60 Creek, 15 lks. wide, 10 ins. deep, in bottom of canyon, course SE., asc. 310 ft. over SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, for Std. cor. of secs. 31 and 32, with brass cap mkd:

S C
T 16 N | R 69 E
S 31 | S 32

1920

from which,

A pinon, 5 ins. diam., bears N.63 $\frac{3}{4}$ °E., 35 lks., dist., mkd. SC T16N R69E S32 SC BT
A pinon, 12 ins. diam., bears N.79 $\frac{1}{2}$ °W., 56 lks., dist., mkd. SC T16N R69E S31 SC BT

Land, mountainous.

Soil, rocky; limestone formation.

Undergrowth, sagebrush. Timber, pinon pine, mahogany, Fair grazing. cedar.