

Survey of the N. Bdy. of T. 22 N., R. 70 E.

Chains. Asc. S.W. slope 202 ft. to

54.66 Intersect the Nevada-Utah state line at a point,
 N.0° 44' E., 14 lks. dist. from the temp. point for the
 cor. of Ts. 22 and 23 N., R. 70 E., previously set on
 the Nevada-Utah state line.
 Set an iron post, 3 ft. long, 3 ins. in dia., 6 ins. in
 the ground, to bed rock, in a mound of stone, for the
 cor. of Ts. 22 and 23 N., R. 70 E., with brass cap mkd.

T23N
R70E
S34
S3
T22N
1922

from which

a pinon pine 10 ins. in dia. bears S.65 $\frac{1}{2}$ ° W., 40 lks.
 dist., marked T 22 N R 70 E S 34 B T

a mahogany 4 ins. in dia. bears N.73° W., 89 lks. dist.,
 marked T 23 N. R 70 E S 34 B T

Land, rough mountainous. Soil, rocky clay loam.
 Undergrowth, sage and bunch grass.
 Timber, pinon pine, cedar and mahogany.

Subdivisions of T. 22 N., R. 70 E.

From the cor. of secs. 5 and 6, 31 and 32, on the
 S.Bdy. of twp., which is an iron post, 3 ins. in dia.,
 firmly set and properly marked and witnessed.
 N.0° 01' E., on a true line, bet. secs. 31 and 32.

Asc. S.W. slope over rough mountainous land covered
 with medium and dense growth of cedar, pinon pine and
 mahogany timber.

6.30 Top of spur, 47 ft. above sec. cor., projects W.
 Desc. W. slope.

22.70 Dry wash, 185 ft. below spur, course W.
 Asc. S.W. slope

26.20 Top of spur, 25 ft. above wash, projects W.
 Desc. W. slope.

30.80 Dry wash, 30 ft. below spur, course S.W.