

Subdivisions of T. 22 N., R. 70 E.

Chains.

Desc. N. slope 28 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 20 ins. in the ground to bed rock, in a mound of stone, for the cor. of secs. 17 and 18, 19 and 20, with brass cap mkd.

T22N	R70E
S18	S17
S19	S20
1922	

from which

a mahogany 9 ins. in dia. bears N. $43\frac{1}{2}^{\circ}$ E., 338 lks.

dist., marked T 22 N R 70 E S 17 B T

a mahogany 7 ins. in dia. bears S. $79\frac{1}{2}^{\circ}$ E., 270 lks.

dist., marked T 22 N R 70 E S 20 B T

a cedar 6 ins. in dia. bears S. 64° W., 300 lks. dist.,

marked T 22 N R 70 E S 19 B T

a pinon pine 6 ins. in dia. bears N. 24° W., 294 lks.

dist., marked T 22 N R 70 E S 18 B T

Land, rough mountainous. Soil, rocky clay loam.

Undergrowth, sage and bunch grass.

Timber, pinon pine, cedar and mahogany.

N. $89^{\circ} 49'$ W., on a random line, bet. secs. 18 and 19.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.20 Intersect the cor. of secs. 13 and 18, 19 and 24, which is an iron post, 3 ins. in dia., firmly set, and properly marked and witnessed.

Thence

S. $89^{\circ} 49'$ E., on a true line, bet. secs. 18 and 19.

Desc. S.E. slope over rolling mountainous land, through medium growth of pinon pine and cedar timber.

16.00 Dry wash, 292 ft. below sec. cor., course S.W.

Asc. S.W. slope.

32.00 Top of spur, 157 ft. above wash, projects S.W.

Desc. S.E. slope 41 ft. to

40.10 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S18
$\frac{1}{4}$
S19
1922