

Subdivisions of T. 22 N., R. 70 E.

Chains.

S18 | S17
1922

from which

a pinon pine 10 ins. in dia. bears N.72³/₄° E., 26 lks. dist., marked ¹/₄ S 17 B T

a pinon pine 5 ins. in dia. bears N.87° W., 32 lks. dist., marked ¹/₄ S 18 B T

63.80 Top of spur-ridge, 261 ft. above ¹/₄ sec. cor., bears E. and W. Desc. N.W. slope.

71.40 Dry wash, 41 ft. below spur-ridge, course N.W. Asc. S.W. slope.

74.50 Top of spur, 18 ft. above wash, projects W. Desc. N.W. slope 35 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 7 and 8, 17 and 18, with brass cap mkd.

T22N | R70E
S7 | S8
S18 | S17
1922

from which

a mahogany 4 ins. in dia. bears N.75° E., 28 lks. dist., marked T 22 N R 70 E S 8 B T

a pinon pine 10 ins. in dia. bears S.34° E., 7-lks. dist., marked T 22 N R 70 E S 17 B T

a cedar 10 ins. in dia. bears S.35° W., 10 lks. dist., marked T 22 N R 70 E S 18 B T

a mahogany 5 ins. in dia. bears N.20° W., 32 lks. dist., marked T 22 N R 70 E S 7 B T

Land, rolling mountainous. Soil, rocky clay loam.

Undergrowth, sage, shadscale and bunch grass.

Timber, pinon pine, cedar and mahogany.

N.89° 49' W., on a random line, bet. secs. 7 and 18.

40.00 Set temp. ¹/₄ sec. cor.

80.14 Intersect the cor. of secs. 7 and 12, 13 and 18, which is an iron post, 3 ins. in dia., firmly set, and properly marked and witnessed.