

Subdivisions of T. 22 N., R. 70 E.

Chains.  
 42.00 Wagon road bears NE. and SW.  
 45.00 Weaver creek, dry at this point, 19 ft. below  $\frac{1}{4}$  sec. cor.,  
 course S.W. Asc. S.E. slope.  
 68.00 Top of spur, 287 ft. above Weaver creek, projects S.E.,  
 Desc. N.E. slope.  
 76.50 Dry wash, 35 ft. below spur, course S.E.  
 Asc. S.E. slope 7 ft. to  
 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins.  
 in the ground, for the cor. of secs. 5 and 6, 7 and 8,  
 with brass cap mkd.

T22N R70E  
 S6 | S5  
 S7 | S8  
 1922

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
 of the cor.

Land, rolling mountainous. Soil, rocky clay loam.

Undergrowth, sage and bunch grass.

Timber, scattering pinon pine, cedar and mahogany.

---

N.89° 49' W., on a random line, bet. secs. 6 and 7.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 80.20 Fall 21 lks. S. of the cor. of secs. 1 and 6, 7 and 12,  
 which is an iron post, 3 ins. in dia., firmly set, and  
 properly marked and witnessed.

Thence

S.89° 40' E., on a true line, bet. secs. 6 and 7.

Asc. S.W. slope over rolling mountainous land.

17.50 Top of spur, 273 ft. above sec. cor., projects N.W.  
 Desc. N.E. slope.

30.40 Dry wash, 26 ft. below spur, course N.W.  
 Asc. N.W. slope 125 ft. to

40.10 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in  
 the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S6  
 $\frac{1}{4}$  —————  
 S7  
 1922

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W.  
 of the cor.