

## Subdivisions of T. 22 N., R. 70 E.

Chains.	
41.00	Dry wash, 3 ft. below $\frac{1}{4}$ sec. cor., course N.W. Asc. N.W. slope.
68.90	Top of spur-ridge, 292 ft. above wash, bears N.E. and S.W. Desc. S.E. slope.
69.90	Wagon road, 15 ft. below spur-ridge, bears N.E. and S.W. Desc. S.E. slope 99 ft. to
80.23	The cor. of secs. 5 and 6, 7 and 8. Land, rolling mountainous. Soil, rocky clay loam. Undergrowth, sage and bunch grass. Timber, scattering pinon pine, cedar and mahogany.
<hr/> From the cor. of secs. 4 and 5, 32 and 33, on the S. Bdy. of the township, which is an iron post, 3 ins. in dia., firmly set, and properly marked and witnessed.	
N.0° 01' E., on a true line, bet. secs. 32 and 33.	
Asc. S.E. slope over rough mountainous land covered with a medium growth of pinon pine, cedar and mahogany.	
2.60	Top of spur, 34 ft. above sec. cor., projects S.W. Desc. S.W. slope.
10.00	Dry wash, 97 ft. below spur, course S.W. Asc. S.E. slope.
26.00	Top of spur, 406 ft. above wash, projects S.W. Desc. S.W. slope 67 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
$\begin{array}{c} \frac{1}{4} \\   \\ \text{S32} \text{---} \text{S33} \\   \\ 1922 \end{array}$	
from which	
a mahogany 5 ins. in dia. bears S.16° E., 448 lks. dist., marked $\frac{1}{4}$ S 33 B T	
a pinon pine 6 ins. in dia. bears N.16 $\frac{1}{2}$ ° W., 274 lks. dist., marked $\frac{1}{4}$ S 32 B T	
Asc. S.E. slope 7 ft. to	
45.40	Top of spur-ridge, bears E. and W. Desc. N.W. slope.