


## Subdivisions of T. 22 N., R. 70 E.

Chains.



- from which
- a pinon pine 7 ins. in dia. bears S.  $22\frac{1}{2}^{\circ}$  E., 105 lks.  
dist., marked  $\frac{1}{4}$  S 4 B T
- a pinon pine 12 ins. in dia. bears S.  $73^{\circ}$  W., 126 lks.  
dist., marked  $\frac{1}{4}$  S 5 B T
- 45.30 Dry wash, 30 ft. below  $\frac{1}{4}$  sec. cor., course N.E.  
Asc. N.E. slope.
- 51.30 Top of spur, 70 ft. above wash, projects N.E.  
Desc. S.E. slope.
- 64.30 Dry wash, 30 ft. below spur, course N.E.  
Asc. N.E. slope.
- 77.40 Dry wash, 210 ft. above wash, course N.E.  
Asc. N.W. slope 50 ft. to
- 80.30 The cor. of secs. 4 and 5, 8 and 9.  
Land, rough mountainous. Soil, rocky clay loam.  
Undergrowth, sage and bunch grass.  
Timber, pinon pine, cedar and mahogany.
- 
- From the cor. of secs. 3 and 4, 33 and 34, on the S.Bdy. of township, which is an iron post, 3 ins. in dia. firmly set, and properly marked and witnessed.  
N.  $0^{\circ} 02'$  E., on a true line, bet. secs. 33 and 34.  
Asc. S.E. slope over rough mountainous land, through dense pinon pine, cedar and mahogany timber.
- 15.60 Dry wash, 120 ft. above sec. cor., course S.E.  
Asc. S.E. slope.
- 28.50 Top of spur, 370 ft. above wash, projects S.E.  
Desc. N.E. slope.
- 39.90 Dry wash, 440 ft. below spur, course S.E.  
Asc. S.E. slope, 10 ft. to
- 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 6 ins. in the ground, to solid rock, in a mound of stone, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.