


SURVEY OF E. BOUNDARY OF T. 12 N., R. 51 E.

CHAINS



Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.


42.98 Spur, 20 ft. above draw, projects W., desc. NW. slope.

60.26 Draw, 15 ft. below spur, drains W., asc. SW. slope.

69.10 Spur, 60 ft. above draw, projects W., desc. NW. slope.

76.50 Draw, 130 ft. below spur, drains W., asc. SW. slope, 35 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 6 ins. in the ground, over a marked stone, surrounded by a mound of stone, for the cor. of secs. 1, 6, 7 and 12, with brass cap marked



Land, rolling. Soil, rocky to gravelly. Timber, pinon and cedar. Undergrowth, sage. General drainage, W.


North, on E. bdy. of secs. 1.

Over rolling land. Asc. gradual SW. slope.

6.62 Spur, 50 ft. above sec. cor., projects W., desc. NW. slope.

27.00 Hollow, 95 ft. below spur, drains W., asc. SW. slope 15 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in the ground, over a marked stone, surrounded by a mound of stone, for ¼ sec. cor., with brass cap marked



Thence over gently rolling land.

80.00 Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins in the ground, for the cor. of Tps. 12 and 13 N., Rs. 51 and 52 E., with brass cap marked