

Chains

From the cor. of Tps. 37 and 38 N., Rs. 23 $\frac{1}{2}$ E. and 24 E. described in Book "A" T. 38 N., R. 24 E. under this group.

North, on a true line, bet. secs. 31 and 36.

Over nearly level land, through dense undergrowth.


2.30 Road, bears N. 10° W. and S. 10° E., desc. 30 ft. over Gradual W. slope.

20.00 Head of gulch, course N. 70° W., asc. 80 ft. over S. slope.

29.60 Spur, slopes W., desc. 130 ft. over NW. slope.

39.10 Gulch, course NE., asc. 15 ft. over S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.




and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

59.20 Ravine, course E. 5.00 chs., thence N., asc. 40 ft. over SE. slope.

61.90 Spur and top of small perpendicular bluff facing S., bears E. and W., desc. 10 ft.

64.90 Head of small gulch, course E., asc. 80 ft. over S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 10 ins. in the ground, to bed rock and 14 ins. in a mound of stone, for cor. of secs. 25, 30, 31 and 36, with brass cap mkd.



Deposit a small stone, marked (X) at base of cor.

Land, level and rolling. Soil, light sandy shallow coarse gravel and rocky loam. Undergrowth, sagebrush and very little grass.

North, on a true line, bet. secs. 25 and 30.

Asc. 20 ft. over S. slope, through dense undergrowth.

4.00 Spur, slopes E. asc. 60 ft. over broken SE. slope.