

DEPENDENT

RESURVEY OF THE FOURTH STD. PAR. S. THRU RANGE 49 EAST 40 WEST.

CHAINS

distances, none of which were found until at  
 158.88 Fall 60 lks. S. of the orig. Std.  $\frac{1}{4}$  sec. cor. of sec.  
 32, which is a cottonwood stake, 1 ins diam., one side  
 surfaced on which " $\frac{1}{4}$  S" is distinct. Stake lying on  
 side of small mound of earth, which is accepted as the  
 point for the Std.  $\frac{1}{4}$  cor. of sec. 32. The true course  
 of this line is S.89°47'W., and the length of each half  
 mile is 39.72 chs.

-----  
 TRUE LINE.

To restore the Std. cor. of T.16 S., Rs. 49 and 50 E.,  
 at a point N.89°47'E., 39.72 chs. distant from the Std.  
 $\frac{1}{4}$  sec. cor. of sec. 36, I set an iron post, 3 ft. long,  
 3 ins. diam., 24 ins. in the ground, for the restored  
 cor. of T. 16 S., Rs. 49 and 50 E., with brass cap mkd:

S C	
T16 S.	
R 49 E	R 50 E
S 36	S 31

1921

dig pits, 18x18x12 ins. N., E. and W. of cor., 3 ft.  
 dist.

Thence

S.89°47'W., on true line,

Over level land thru dense undergrowth,

27.65 Road, bears NE. and SW.

39.72 The orig. Std.  $\frac{1}{4}$  sec. cor. of sec. 36, which is a granite  
 stone, 12x10x6 ins. in a mound of stone, mkd.  $\frac{1}{4}$  on N.  
 face. Destroy orig. marks and mark AP on N. face.

Thence, N.89°05'W., on true line, with continuous measure-  
 ment,

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
 the ground, for Std.  $\frac{1}{4}$  sec. cor. of sec. 36, with  
 brass cap mkd:

S C	
$\frac{1}{4}$ S	36

. 1921

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high,