

DEPENDENT

RESURVEY OF THE FOURTH STD. PAR. S. THRU RANGES 49 EAST 10 EAST.

CHAINS

Thence

N.89°50' W., with continuous measurement,

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for Std. cor. of secs. 31 and 32, with brass cap mkd:

	S	C
T16S		R49E
S 31		S 32

1921

dig pits, 18x18x12 ins., N. E. and W. of cor., 3 ft. dist.

Land, level.

Soil, sandy and gravelly, gravelly formation, 2nd rate.

Undergrowth, creosote brush, shad scale, greasewood.

No timber.

From the Std. cor. of secs. 31 and 32.

N.89°50' W., on S. bdy. of sec. 31,

Over level land thru dense undergrowth.

12.00 Sandy wash, course S.25°W.

38.16 The orig. Std. $\frac{1}{4}$ sec. cor. of sec. 31, which is a basalt stone, 10x8x8 ins., set in a mound of earth, mkd. $\frac{1}{4}$ on N. face which I efface and mark AP on N. face.

Thence

S.89°51' W., with continuous measurement,

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for Std. $\frac{1}{4}$ sec. cor. of sec. 31, with brass cap mkd:

	S	C
$\frac{1}{4}$ S 31		

1921

dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist.

62.11 At proportionate distance, set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for restored closing cor. of T.17 S., Rs. 48 and 49 E., with brass cap mkd:

T16S	R49 E
S 31	

S 1		S 6
R48E		R49E

CC

T17S

1921