

## ESTABLISHMENT OF CORNERS ON N. BOUNDARY OF T. 8 N., R. 29 E.

CHAINS Set an iron post, 3 ft. long, 1 in. in dia., 14 ins. in the ground on solid rock, over a marked stone and surrounded by a mound/stone, for  $\frac{1}{4}$  sec. cor. sec. 5, with brass cap marked

$\frac{1}{4}$  S5  
1920

Cor. sets on steep rocky E. slope, about 185 ft. above  $\frac{1}{4}$  sec. cor. sec. 32.

NOTE: Cors. for subdivisions in T. 9 N., R. 29 E., were set by me in the execution of survey of Group No. 65 in 1919.

NOTE: The latitudinal outboundary bet. secs. 14 and 23, 15 and 22, 9 and 16, 8 and 17 exceeded the limit of 10 minutes from the cardinal; therefore governing sectional correction lines were run as follows: Beginning at the cor. of secs. 11, 12, 13 and 14, thence, west on a true latitudinal curve to an intersection with the limiting outboundary bet. secs. 15 and 16, where a cor. for the two secs. 10 and 15 was established. The intermediate quarter-section and section cors. were set at regular intervals of 40 chs., throwing the fractional measurement against the old work. Beginning at the cor. of secs. 3, 4, 9 and 10, the same procedure was followed in projecting sectional correction line bet. secs. 4 and 9, and 5 and 8, setting cor. for the two sections 5 and 8 at intersection with the limiting outboundary bet. sec. 7 and 8.

## INDEPENDENT RESURVEY OF SUBDIVISIONS OF T. 8 N., R. 29 E.

From the cor. of secs. 13, 14, 23 and 24, heretofore described

East on a random line bet. secs. 13 and 24

40.00 Set temp  $\frac{1}{4}$  sec. cor.

40.20 Record dist., no trace of old  $\frac{1}{4}$  sec. cor.

80.28 The cor. of secs. 13, 18, 19 and 24, T. 8 N., Rs. 29 and 30 E., which is a 2 in. iron post, firmly set 12 ins. above the ground, and marked and witnessed as described by the Surveyor General

Thence

West, on a true line bet. secs. 13 and 24

Slight ascent

1.60 Wash, drains N. 85° E., 3 ft. wide, 12 ins deep, thence along N. side of wash.