

## DEPENDENT RESURVEY OF PORTION OF W. BOUNDARY OF T. 8 N., R. 30 E.

CHAINS	Beginning at the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of twp., hereinbefore described. Thence N 0° 15' E., on resurvey line bet. secs. 25 and 30. Descend NE. slope 65 ft. 4.80 Gulch, drains NE., ascend SE. slope. 13.90 Spur, 385 ft. above gulch, projects E., thence along broken NE. slope. 19.80 Begin steep descent of 110 ft. along NE. slope. 23.40 Draw, drains SE., ascend SE. slope. 27.00 Spur, 65 ft. above draw, projects E., descend along broken E. slope. 39.89 The old $\frac{1}{4}$ sec. cor., which is a stone, 18X10X6 ins., marked and witnessed as described by the Surveyor General. Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, alongside old cor. for $\frac{1}{4}$ sec. cor. of secs. 25 and 30, with brass cap marked <div style="text-align: center;"><math>\frac{1}{4}</math> S25   S30 1919</div> Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Thence N 0° 07' E., with continuous measurement 57.20 Draw, drains NE., 110 ft. below spur, ascend SE. slope. 64.50 Spur, 55 ft. above draw, projects NE., descend along NW. slope. 74.50 Draw, 205 ft. below spur, drains NE., ascend 85 ft. to cor. 80.08 The cor. of secs. 19, 24, 25 and 30, which is a stone, 24X18X10 ins., firmly set in a mound of stone, marked and witness <sup>ed</sup> as described by the Surveyor General. Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground, alongside old cor., for the cor. of secs. 19, 24, 25 and 30, with brass cap marked
--------	--